



PRODUKTBESCHREIBUNG


- » Hochleistungs-Fräser mit ungleicher Teilung und Zentrumsschnitt
- » Schneidenlänge 3xd
- » Freigestellt nach der Schneide

MATERIAL


» VHM, TiAlN Multilayer-beschichtet




Z	d2	d3	l	l1	l2	C	d	Nr.	EUR
5	3,7	6	65	12	26	0,05	4	WZF 13256/ 4	< >
5	4,7	6	65	15	26	0,05	5	WZF 13256/ 5	< >
5	5,5	6	65	18	28	0,05	6	WZF 13256/ 6	< >
5	7,5	8	75	24	38	0,1	8	WZF 13256/ 8	< >
5	9,2	10	80	30	38	0,1	10	WZF 13256/10	< >
5	11,2	12	93	36	46	0,1	12	WZF 13256/12	< >
5	15	16	108	48	58	0,15	16	WZF 13256/16	< >
5	19	20	126	60	74	0,15	20	WZF 13256/20	< >




RICHTWERTE HPC-FRÄSEN

WZF 13246	Werkstoff	Festigkeit	Vc ¹ m/min.	d								
				4	5	6	8	10	12	16	20	25
				fz ² (mm/z)								
 <p>ae = 0.20 x d ap = 1 x d</p>	1.1730	640 N/mm ²	220	0.023	0.027	0.031	0.061	0.077	0.094	0.110	0.132	0.187
	1.2083	780 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2085	1080 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2162	660 N/mm ²	220	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	1.2311	1080 N/mm ²	160	0.017	0.020	0.022	0.044	0.056	0.068	0.080	0.096	0.136
	1.2312	1080 N/mm ²	165	0.016	0.018	0.021	0.041	0.053	0.064	0.075	0.090	0.128
	1.2316	1010 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2343	780 N/mm ²	175	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	1.2379	780 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2714HH	1350 N/mm ²	110	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2767	830 N/mm ²	165	0.020	0.023	0.027	0.052	0.067	0.081	0.095	0.114	0.162
	1.2842	775 N/mm ²	165	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	Stahl	1400 N/mm ²	110	0.012	0.013	0.015	0.030	0.039	0.047	0.055	0.066	0.094

RICHTWERTE HSC-FRÄSEN


WZF 13256	Werkstoff	Festigkeit	Vc ¹ m/min.	d								
				4	5	6	8	10	12	16	20	25
				fz ² (mm/z)								
 <p>ae = 0.1 x d ap = 2.5 x d</p>	1.1730	640 N/mm ²	220	0.023	0.027	0.031	0.061	0.077	0.094	0.110	0.132	0.187
	1.2083	780 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2085	1080 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2162	660 N/mm ²	220	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	1.2311	1080 N/mm ²	160	0.017	0.020	0.022	0.044	0.056	0.068	0.080	0.096	0.136
	1.2312	1080 N/mm ²	165	0.016	0.018	0.021	0.041	0.053	0.064	0.075	0.090	0.128
	1.2316	1010 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2343	780 N/mm ²	175	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	1.2379	780 N/mm ²	145	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2714HH	1350 N/mm ²	110	0.015	0.017	0.019	0.021	0.027	0.033	0.039	0.046	0.065
	1.2767	830 N/mm ²	165	0.020	0.023	0.027	0.052	0.067	0.081	0.095	0.114	0.162
	1.2842	775 N/mm ²	165	0.021	0.025	0.028	0.055	0.070	0.085	0.100	0.120	0.170
	Stahl	1400 N/mm ²	110	0.012	0.013	0.015	0.030	0.039	0.047	0.055	0.066	0.094

RICHTWERTE SCHLICHTEN

WZF 13246 WZF 13256	Werkstoff	Festigkeit	Vc ¹ m/min.	d								
				4	5	6	8	10	12	16	20	25
				fz ² (mm/z)								
 <p>ae = 0.05 x d ap = 2 x d</p>	1.1730	640 N/mm ²	300	0.017	0.017	0.021	0.044	0.061	0.072	0.088	0.105	0.154
	1.2083	780 N/mm ²	195	0.015	0.017	0.019	0.017	0.023	0.027	0.034	0.040	0.059
	1.2085	1080 N/mm ²	195	0.015	0.017	0.019	0.017	0.023	0.027	0.034	0.040	0.059
	1.2162	660 N/mm ²	300	0.017	0.017	0.021	0.040	0.055	0.065	0.080	0.095	0.140
	1.2311	1080 N/mm ²	220	0.015	0.017	0.019	0.032	0.044	0.052	0.064	0.076	0.112
	1.2312	1080 N/mm ²	225	0.015	0.017	0.019	0.030	0.041	0.049	0.060	0.071	0.105
	1.2316	1010 N/mm ²	195	0.015	0.017	0.019	0.017	0.023	0.027	0.034	0.040	0.059
	1.2343	780 N/mm ²	240	0.017	0.017	0.021	0.040	0.055	0.065	0.080	0.095	0.140
	1.2379	780 N/mm ²	195	0.015	0.017	0.019	0.017	0.023	0.027	0.034	0.040	0.059
	1.2714HH	1350 N/mm ²	140	0.015	0.017	0.019	0.017	0.023	0.027	0.034	0.040	0.059
	1.2767	830 N/mm ²	225	0.017	0.017	0.021	0.038	0.052	0.062	0.076	0.090	0.133
	1.2842	775 N/mm ²	225	0.017	0.017	0.021	0.040	0.055	0.065	0.080	0.095	0.140
	Stahl	1400 N/mm ²	140	0.014	0.016	0.018	0.024	0.033	0.039	0.048	0.057	0.084

1) Vc: Schnittgeschwindigkeit (m/min.)

2) fz: Vorschub pro Schneide (mm/z)

 Weitere Materialien und Schnittwerte finden Sie im Schnittdaten-Kalkulator