



PRODUCT DESCRIPTION

- » Highest process security and reliable temperature regulation through state-of-the-art hardware and software components
- » Ergonomic and intuitive operation with multi-touch screen
- » Compact design for minimal space requirements
- » High-end features such as intelligent power regulation, MoldCheck, and much more

L	B	H	Wt.	CEE mains connection	Maximum output	Number of zones	Pin assignment	No.	EUR
260	390	400	21 kg	16 A	11 kW	6	MEU	RH 1000/ 6/D024/ 7/001/WI24B/ 16A	<>
260	390	400	22 kg	32 A	22 kW	12	MEU	RH 1000/ 12/D024/ 7/001/WI24B/ 32A	<>
260	390	400	23 kg	63 A	43 kW	18	MEU	RH 1000/ 18/D024/ 7/001/WI24B/ 63A	<>
260	390	400	24 kg	63 A	43 kW	24	MEU	RH 1000/ 24/D024/ 7/001/WI24B/ 63A	<>
450	390	400	30 kg	63 A	43 kW	30	MEU	RH 1000/ 30/D048/ 7/001/WI24B/ 63A	<>
450	390	400	32 kg	63 A	43 kW	36	MEU	RH 1000/ 36/D048/ 7/001/WI24B/ 63A	<>
450	390	400	32 kg	63 A	43 kW	42	MEU	RH 1000/ 42/D048/ 7/001/WI24B/ 63A	<>
450	390	400	34 kg	63 A	43 kW	48	MEU	RH 1000/ 48/D048/ 7/001/WI24B/ 63A	<>
260	390	400	21 kg	16 A	11 kW	6	121	RH 1000/ 6/D024/ 7/121/WI24B/ 16A	<>
260	390	400	22 kg	32 A	22 kW	12	121	RH 1000/ 12/D024/ 7/121/WI24B/ 32A	<>
260	390	400	23 kg	63 A	43 kW	18	121	RH 1000/ 18/D024/ 7/121/WI24B/ 63A	<>
260	390	400	24 kg	63 A	43 kW	24	121	RH 1000/ 24/D024/ 7/121/WI24B/ 63A	<>
450	390	400	30 kg	63 A	43 kW	30	121	RH 1000/ 30/D048/ 7/121/WI24B/ 63A	<>
450	390	400	32 kg	63 A	43 kW	36	121	RH 1000/ 36/D048/ 7/121/WI24B/ 63A	<>
450	390	400	35 kg	63 A	43 kW	42	121	RH 1000/ 42/D048/ 7/121/WI24B/ 63A	<>
450	390	400	34 kg	63 A	43 kW	48	121	RH 1000/ 48/D048/ 7/121/WI24B/ 63A	<>
260	390	400	21 kg	16 A	11 kW	6	522	RH 1000/ 6/D024/ 7/522/WI24B/ 16A	<>
260	390	400	22 kg	32 A	22 kW	12	522	RH 1000/ 12/D024/ 7/522/WI24B/ 32A	<>
260	390	400	23 kg	63 A	43 kW	18	522	RH 1000/ 18/D024/ 7/522/WI24B/ 63A	<>
260	390	400	24 kg	63 A	43 kW	24	522	RH 1000/ 24/D024/ 7/522/WI24B/ 63A	<>
450	390	400	34 kg	63 A	43 kW	48	522	RH 1000/ 48/D048/ 7/522/WI24B/ 63A	<>
260	390	400	21 kg	16 A	11 kW	6	620	RH 1000/ 6/D024/ 7/620/HA16 / 16A	<>
260	390	400	22 kg	32 A	22 kW	12	620	RH 1000/ 12/D024/ 7/620/HA16 / 32A	<>
260	390	400	23 kg	63 A	43 kW	18	620	RH 1000/ 18/D024/ 7/620/HA16 / 63A	<>
260	390	400	24 kg	63 A	43 kW	24	620	RH 1000/ 24/D024/ 7/620/HA16 / 63A	<>

SPECIAL DESIGNS AVAILABLE:

Pin assignment: special pin assignment possible on request

For custom-made products or specific questions, simply contact Meusburger for professional specialist advice

