



PRODUCT DESCRIPTION


- » Optimal running smoothness due to hard turned shanks
- » With Balluff chip hole

APPLICATION

- » For clamping tools with cylindrical shank according to DIN 1835 type B and DIN 6359 type HB

INCLUDED IN THE DELIVERY

- » Includes clamping screw



l	M	d	Interface	d1	A	No.	EUR
35	M6	25	SK 40	6	50	HWZ 2201/SK40/ 6/ 50	<>
35	M8	28	SK 40	8	50	HWZ 2201/SK40/ 8/ 50	<>
41	M10	35	SK 40	10	50	HWZ 2201/SK40/10/ 50	<>
48	M12	42	SK 40	12	50	HWZ 2201/SK40/12/ 50	<>
48	M12	44	SK 40	14	50	HWZ 2201/SK40/14/ 50	<>
51	M14	48	SK 40	16	63	HWZ 2201/SK40/16/ 63	<>
51	M14	48	SK 40	18	63	HWZ 2201/SK40/18/ 63	<>
53	M16	52	SK 40	20	63	HWZ 2201/SK40/20/ 63	<>
60	M18x2	65	SK 40	25	100	HWZ 2201/SK40/25/100	<>
64	M20x2	72	SK 40	32	100	HWZ 2201/SK40/32/100	<>